

Application

CAREFULLY EXAMINE THIS WALLCOVERING FOR COLOUR, DESIGN, QUANTITY AND IMPERFECTIONS BEFORE INSTALLING.

SURFACE PRERARATION: Old wallpaper should be removed. Walls should be clean, dry, and smooth. Prepare surface with a premixed, universal wallcovering primer.

1. Measuring from corner to corner of your starting wall, mark a vertical plumb line at a distance of 1" / 2.5 cm less than the paper width.

2. Cut your first strip of wallpaper 4" / 10 cm longer than the wall height you intend to cover.

3. **FOR PRE-PASTED PAPER:** Roll cut strip loosely with the pattern side up, paste side out. Submerge rolled strip in warm water for 30 seconds to activate paste (or optionally, brush on a pre-pasted activator)

FOR UNPASTED PAPER: Using a clean, light-medium weight, pre-mixed adhesive, apply an even film of paste to the back of the paper, moving the paste brush or applicator from the center to the edge.

4. Fold moistened strip paste-to-paste, and allow to set for 3 minutes.

5. Carry the wallcovering to the wall. Place one edge of your strip along the vertical plumb line and allow the remainder of the strip to go into and around corner.

6. Smooth out bubbles using a smoothing brush. Trim top and bottom with a straight edge and razor knife. Wipe each strip clean with clean water and sponge.

7. Using pattern match at baseboard and ceiling as reference, determine the length of your next strip, allowing extra for trimming. Then follow steps #2 and #3 above.

8. Slide the next strip into position with its edge butted against the edge of the preceding strip. Do not overlap seams. Gently roll butted seams with a seam roller. Be sure to match design of the adjacent strip at eye level. Repeat steps #6, #7, and #8.

NOTE: Reverse hang strips of wallcovering on random matched textures.